

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the claims

1. (currently amended) An implantable prosthesis, comprising:
 - (a) a prosthetic component having first and second surfaces, wherein the second surface ~~adapted to be~~ is oriented toward a bone in which the component is to be implanted;
 - (b) at least one opening extending from the first surface to the second surface; the opening ~~adapted to receive more than one type of insertion member and~~ comprising (i) an extended nonthreaded frustoconical taper section extending ~~from the first surface through a~~ substantial portion of the opening and (ii) a rounded section ~~at the second surface beginning at a narrow end of the frustoconical taper section and~~ having a smaller diameter than the frustoconical taper section ~~portion of the taper at the first surface, wherein the opening adapted to accommodate an insertion member at multiple orientations relative to the component; and~~
 - (c) an insertion member having a head which includes a rounded, nonfrustoconical contact surface ~~adapted to that~~ contacts said frustoconical taper section of said opening when the insertion member is inserted into the opening, the insertion member adapted to be inserted into the opening such that the contact surface contacts the extended frustoconical taper section;

whereby the insertion member ~~is adapted to fits~~ in the opening in a substantially fluid tight relationship, at a plurality of angular orientations between the insertion member and the

opening, ~~so that~~ and the head of the insertion member does not protrude beyond the first surface.

2. (currently amended) The implantable prosthesis of claim 1, wherein once the appropriate orientation of the insertion member is selected, the insertion member ~~is adapted to be locked~~ locks relative to the frustoconical taper section ~~such that the head of the insertion member does not protrude beyond the first surface.~~

3. (currently amended) The implantable prosthesis of claim 1, wherein the rounded section ~~at the second surface is a flat edge, a chamfered edge, a beveled surface, a curved surface,~~ a rounded surface, or a spherical surface.

4. (previously presented) The implantable prosthesis of claim 1, wherein the head of the insertion member comprises an outer edge that is spherical, near-spherical, toroidal, elliptical, global, slightly curved, or rounded.

5. (original) The implantable prosthesis of claim 1, wherein the insertion member comprises one or more of a bone screw, a bone peg, a bone spike, or an aperture cover.

6. (previously presented) The implantable prosthesis of claim 1, wherein the contact surface of the insertion member head is part of a sphere.

7. (currently amended) The implantable prosthesis of claim 1, wherein the opening has an inner wall, the head has an outer rim, and wherein the insertion member ~~is adapted to be inserted into the opening at an angle while maintaining~~ maintains a constant point of contact between the inner wall and the outer rim when the insertion member is inserted into the opening at an angle.

8. (original) The implantable prosthesis of claim 1, wherein the prosthesis comprises a hip replacement system and wherein the first and second surfaces are surfaces of an acetabular cup.

9. (canceled)

10. (previously presented) The implantable prosthesis of claim 1, wherein the opening is a universal-type opening and wherein the insertion member comprises any one of bone screw, a bone peg, a bone spike, or an aperture cover, wherein any one of the bone screw, a bone peg, a bone spike, or an aperture cover comprises a universal-type contact surface that corresponds to the universal-type opening.

11. (canceled)

12. (canceled)

13. (currently amended) An acetabular implant for fixation to a patient, comprising:

(a) an acetabular cup having an inner surface, an outer surface, and at least one opening extending from the inner surface to the outer surface, wherein the outer surface ~~adapted to be~~ is oriented toward a bone in which the component is to be implanted;

(b) the at least one opening having an extended nonthreaded frustoconical tapered section ~~beginning at the inner surface~~ that extends through a substantial portion of the opening; and

(c) an insertion member for insertion into the opening, the member comprising a head, which includes a rounded, nonfrustoconical contact surface ~~adapted to that~~ contacts said frustoconical tapered section of said opening, ~~the insertion member adapted to be inserted into the opening whereby the contact surface contacts the extended frustoconical tapered section;~~

wherein the at least one opening ~~is adapted to~~ accommodates more than one type of insertion member, and

whereby the insertion member ~~is adapted to~~ fits in the opening in a substantially fluid tight relationship, at a plurality of angular orientations between the insertion member and the opening, ~~so that~~ and the head of the insertion member does not protrude beyond the inner surface of the cup.

14. (currently amended) The acetabular implant of claim 13, wherein once the appropriate orientation of the insertion member is selected, the insertion member ~~is adapted~~

~~to be locked locks~~ relative to the frustoconical taper section ~~such that the head of the~~
~~insertion member does not protrude beyond the inner surface.~~

15. (previously presented) The acetabular implant of claim 13, wherein the head comprises an outer edge that is spherical, near-spherical, toroidal, elliptical, global, slightly curved, or rounded.

16. (currently amended) The acetabular implant of claim 13, wherein the opening has an inner wall, the head has an outer rim, and wherein the insertion member is ~~adapted to be inserted into the opening at an angle while maintaining~~ maintains a constant point of contact between the inner wall and the outer rim when the insertion member is inserted into the opening at an angle.

17. (previously presented) The acetabular implant of claim 13 further comprising a femoral stem and a cup liner.

18. (original) The acetabular implant of claim 13, wherein the insertion member comprises a bone screw, a bone peg, a bone spike, or an opening cover.

19. (canceled)

20. (canceled)

21. (canceled)

22. (canceled)

23. (canceled)

24. (canceled)

25. (currently amended) An acetabular implant for fixation to a patient, comprising:

(a) an acetabular cup having an inner surface, an outer surface, and at least one opening extending from the inner surface to the outer surface,

(b) the at least one opening having an extended nonthreaded frustoconical tapered section beginning at the inner surface extending through a substantial portion of the opening and a second rounded section at the outer surface beginning at a narrow end of the frustoconical taper section and having a diameter smaller than the diameter of the opening at the inner surface;

(c) an insertion member for insertion into the opening, the insertion member comprising a head, which includes a rounded, nonfrustoconical contact surface adapted to that contacts said frustoconical tapered section of said opening, the insertion member adapted to be inserted into the opening such that the contact surface contacts the extended frustoconical tapered section when the insertion member is inserted into the opening;

wherein the at least one opening is ~~adapted to~~ accommodates more than one type of insertion member; and

whereby the insertion member is ~~adapted to~~ fits in the opening in a substantially fluid tight relationship, at a plurality of angular orientations between the insertion member and the opening, so that the head of the insertion member does not protrude beyond the inner surface of the cup.

26. (original) The acetabular cup of claim 25, further comprising:

- (d) a liner for lining the inner surface of the acetabular cup; and
- (e) a femoral component for insertion into a patient's femur ~~and adapted to that~~ cooperates with the acetabular cup and liner.

27. (currently amended) A method of replacing at least part of a hip joint in a patient, comprising:

- (a) providing an acetabular implant for fixation to a patient, comprising:
 - (1) an acetabular cup having an inner surface, an outer surface, and at least one opening extending from the inner surface to the outer surface;
 - (2) the at least one opening having an extended nonthreaded frustoconical tapered section ~~beginning at the inner surface extending through a substantial portion of the opening~~ and a ~~second rounded section at the outer surface beginning at a narrow end of the~~ frustoconical taper section and having a diameter smaller than the diameter of the opening at the inner surface;

(3) an insertion member for insertion into the opening, the insertion member comprising a head which includes a rounded, nonfrustoconical contact surface ~~adapted to that~~ contacts said frustoconical tapered section of said opening when the insertion member is inserted into the opening, ~~the insertion member adapted to be inserted into the opening such that the contact surface contacts the extended frustoconical tapered section;~~

wherein the at least one opening ~~is adapted to~~ accommodates more than one type of insertion member; and

whereby the insertion member ~~is adapted to fit~~ in the opening in a substantially fluid tight relationship, at a plurality of angular orientations between the insertion member and the opening, ~~so that~~ and the head of the insertion member does not protrude beyond the inner surface of the cup;

- (b) preparing the bone of the patient's hip to receive the acetabular implant; and
- (c) implanting the acetabular implant.

28. (canceled)

29. (original) The method of claim 27, further comprising providing an acetabular cup liner and positioning the acetabular cup liner in the acetabular cup.

30. (previously presented) The method of claim 27, further comprising providing a femoral prosthesis and positioning the femoral prosthesis in a patient's femur, such that the femoral prosthesis can cooperate with the acetabular implant.

31. (currently amended) The method of claim 27, wherein once the appropriate orientation of the insertion member is selected, the insertion member ~~is adapted to be locked~~ locks relative to the frustoconical taper section such that the head of the insertion member does not protrude beyond the first surface.

32. (currently amended) The method of claim 27, wherein the rounded section ~~at the second surface~~ is ~~a flat edge, a chamfered edge, a beveled surface,~~ a curved surface, a rounded surface, or a spherical surface.

33. (previously presented) The method of claim 27, wherein the head comprises an outer edge that is spherical, near-spherical, toroidal, elliptical, global, slightly curved, or rounded.

34. (original) The method of claim 27, wherein the insertion member comprises one or more of a bone screw, a bone peg, a bone spike, or an aperture cover.

35. (previously presented) The method of claim 27, wherein the contact surface of the insertion member head comprises part of a sphere.

36. (currently amended) The method of claim 27, wherein the opening has an inner wall, the head has an outer rim, and wherein the insertion member is ~~adapted to be~~ inserted into the

opening at an angle while maintaining a constant point contact between the inner wall and the outer rim.

37. (previously presented) The method of claim 27, wherein the interface between the contact surface of the head and the extended taper section comprises a liquid-tight seal.

38. (previously presented) The method of claim 27, wherein the opening is a universal-type opening and wherein the insertion member comprises any one of bone screw, a bone peg, a bone spike, or an aperture cover, wherein any one of the bone screw, a bone peg, a bone spike, or an aperture cover comprises a universal-type head that corresponds to the universal-type opening.